

主要产品种类

Main Products Categories

塑料外壳双面金属化聚丙烯膜电容器（DM、SL 类） Double-sided metallised polypropylene film capacitor

特点 Characteristics

- 1、双面金属化聚丙烯膜 Double sided metallized polypropylene film
- 2、损耗小， 内部温升小 Low loss and small inherent temperature rise
- 3、负电容量温度系数 Negative temperature coefficient of capacitance
- 4、优异的阻燃性能 Excellent active and passive flame resistant abilities

性能指标 Specification

额定电压/Rated Voltage	250~2000VDC
额定电容量/Capacitance	0.0001~5μF
容量偏差/Cap. Tolerance	±5%(J)、 ±10%(K)
绝缘电阻/Insulation Resistance	R ≥100000MΩ, C _N ≤0.33μF I.R·C _N ≥30000s, C _N >0.33μF (20℃,100VDC,60s)
损耗角正切值/Dissipation Factor	tanδ≤10×10 ⁻⁴ (1kHz, 20℃)
运行温度/Operating Temperature	-40℃~+105℃ (+85℃~+105℃: decreasing factor 1.25%/℃ for U _R)
气候类别/Climate Category	40/105/56
封装/Encapsulating	PBT塑壳 PBT Plastic Shell
浸渍剂/Impregnant	环氧树脂 Epoxy Resin

客户需要特殊尺寸，请联系我们。
Please contact us if customers require special sizes.